

tesa® Masking 05286 / 05287

tesa® Masking Tape is a general-purpose masking tape. It offers all it takes to achieve precise masking for professional-style painting results. While it offers good adhesion on almost all flat surfaces, it comes with a guarantee for residue-free removal within 4 days with indoor applications.

Main Application

The product is suitable for general purpose applications: masking, holding, sealing, fixing, light duty packaging etc.

Technical Data & Properties

Material	Slightly-creped paper, natural rubber
Total thickness	110µm
Lengths	05286: 50m : 19mm 05287: 50m : 30mm
Elongation at break	10%
Adhesion to steel	2 N/cm
Tensile strength	33 N/cm
Unwind force (roll width >9mm)	2,5 N/roll (30m/min)

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.