

tesa® Duct Tape Extra Power Universal – 56388/56348/56389/56490

tesa® 56388 Extra Power Universal is a multipurpose cloth tape. It consists of a polyethylene film and a woven polyester fabric backing coated with a synthetic rubber adhesive. tesa® 56388 Extra Power Universal is a self-adhesive tape with typical duct tape features for a wide range of applications.

Features:

- Excellent adhesion even on rough surfaces (e.g. brickwork, timber)
- Easy to tear by hand with straight edges
- Waterproof & weather-resistant
- Moisture-resistant
- Smooth & conformable
- Solvent free
- Available in 4 colors: black, white, gray, green.

Main Application

- For simple, everyday solutions and quick and easy repairs
- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more!

Technical Data & Properties

Backing	PET-fabric, laminated with a PE-film
Adhesive	Synthetic rubber
Total thickness	220 µm
Peel adhesion to steel	$\geq 23\text{N}/25\text{mm}$
Elongation at break	30 %
Tensile Strength	100 N/25mm

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.